


Item	Industrial POE Gigabit Ethernet Switch
Model No.	IES3208P-SFP
Description	8 x 10/100/1000Base-T POE to 2 x 1000Base-FX
	

Overview

The Series are Gigabit PoE+ Ethernet switches that come standard with 8 10/100/1000BaseT(X), 802.3af(PoE), and 802.3at(PoE+) compliant Ethernet switches provide up to 36watts of power per PoE+ port.

Features

- Provide 8 x 10/100/1000Base-TX POE port
- 2 x 1000Base-X SFP Slot
- IEEE802.3af/at compliant
- RJ45 support auto MDI/MDI-X function
- Auto-negotiation speed, half/full-duplex
- Store-and-forward
- Wide-range redundant power design
- Support wide operating temperature (-40 °C ~ +85 °C)
- DIN-Rail and Wall-Mounted Installation
- Low power consumption

Technical Specifications

Model	2GX8GT
Input Voltage	100V~240V AC
Power Consumption	Max. 10W full loading without PDs' consumption
Priority Queues	N/A
Number of VLANs	n/a
MAC Table Size	16K
Packet Buffer Size	8M bit
Temperature	Operating Temperature: -40°C to 85°C Storage Temperature: -40°C to 85°C
Humidity	Operating Humidity: 10% to 90% RH Storage Humidity: 5% to 90% RH
Management	N/A
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3x, IEEE802.3ab, IEEE802.3ae
EMI	GB4943-2011
EMS	ESD (IEC 61000-4-2) Level 4 (8K/15K) RS (IEC 61000-4-3) Level 3 (10V/m) EFT (IEC 61000-4-4) Level 3 (1V/2V) CS (IEC 61000-4-6) Level 3 (10V/m) PFMF (IEC 61000-4-8) Level4 (30A/m) Surge (IEC 61000-4-5) Level 4+(4KV/2KV) DIP (IEC 61000-4-11) Level3 (10V)
Dimensions	143X104X48mm (W×H×D)
Weight	1Kg
Mounting	DIN Rail

Order Information

Model No.	Description
IES3208P-SFP	10/100/1000M 2GX8GE POE, SFP Slot,
Note: 1. Power supply provided by user or ordered additionally	