PE924

24 Channel Gigabit POE Injector






Product Description:

The PE924 is 24 Channel gigabit POE Mid-spans (POE injectors). It is designed to fit fully IEEE802.3af and IEEE802.3at standard. Each POE ports can work with equipments that meet IEEE802.3af/IEEE802.3at standards like Voip Phone, PoE APs, IP Phones, IP cameras, etc. The PE924 is a 1U high 19" case-shaped device. It is with the internal industrial power supplies, have two optional power supplies—370W, 720W. All POE ports support both IEEE802.3af and IEEE802.3at Standard; each port can output 30W max. Extend Function: Power lightning protection.

Product Features:

- IEEE802.3af and IEEE802.3at Standard
- 48 Ports—24 Ports data input and 24 ports data+ power output
- Up to 30W of Power on 2-pairs
- Auto-detect of POE IEEE 802.3af/IEEE 802.3at equipment
- Supports 10/100/1000Base-T applications
- · LED indicators power input indication
- Distance up to 100 meters
- Optional internal power supplies: 370W or 720W
- · Easy plug-and-play installation
- EMI standards complies with FCC, CE class B





Product Specifications:

Item	Description
No. of Ports	48(24 data in and 24 POE out)
Pass Through Data Rates	10/100/1000 Mbps
Power over Ethernet Output	Pin Assignment and Polarity:
	1/2 (+), 3/6 (-)
	Output Power Voltage: 48Vdc
	User Port Power: 30W
Input Power Requirements	AC Input Voltage: 100 to 240 Vac
	AC Input Current: 1.3A at 110 Vac
	AC Frequency: 50 to 60 Hz
Power supplies	370W and 720W optional
Indicators	System Indicator: AC Power
	User Indicator: Channel Power
Connectors	Shielded RJ-45, EIA 568A and 568B
Environmental Conditions	Operating Ambient Temperature:-10 to 45°C
	Operating Humidity:
	Maximum 90%, Non-condensing
	Storage Temperature:-20 to 70°C
	Storage Humidity:
	Maximum 95%, Non-condensing
Reliability	MTBF: 100,000 hrs. @25°C
Regulatory Compliance	IEEE 802.3af (PoE), IEEE 802.3at (PoE+)
	RoHS Compliant, CE, FCC
Package	
Unit Size	44*20*4.4cm
Weight	<5.5KG
package	Carton Box
Package	PE924 24 Channel Gigabit POE injector
	User Manual
	Warranty Card
	Power Cord*1
	Rack Mount Kit*2
	Rubber Feet*4

